SOK

Beyond Safety.

GUANGDONG JINLI ELECTRICAL APPLIANCE CO., LTD.
ADD: EAST OF SANAN CROSS BRIDGE, LONGHOU RD, SANAN ZONE, SHUNDE DISTRICT, GUANGDONG PRC
WEBSITE: www.jinli-cn.com
TEL: 0757-25333277 **FAX:** 0757-25333206
E-MAIL: export@jinli.com

ISO9001 ISO14000 CE CB RoHS

SOK

PRODUCT CATALOG

Series M20 & M44



Since 1985

Series M20

M20/ 16A/ 2/ NS

√ Child-proof Shuttered Outlets

SOK | Beyond Safety.

Fire-resisted (850 degrees, equal to Class V0) back-housing material for living parts.

Back-housing parts is made by Nylon PA66. Work normally for more than one decade under the surrounding temperature from -30℃ to 60℃.

Sockets with Temper-Resistant system can be chosen to protect children from electric shock.

Four directions for wiring. Easy installation for different types of cables from M16 to M25.

All switches can be equipped with LED locator as an option.

SOK | Beyond Safety. Series M20

M20/ L1/ 1
1 Gang 1 Way Switch
10AX 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ L1/ 2
1 Gang 2 Way Switch
10AX 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ L1/ 1/ D
1 Gang 1 Way Switch with LED indicator
10AX 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ L4
1 Gang Intermediate Switch
10AX 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ L2/ 1
2 Gang 1 Way Switch
10AX 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ L2/ 1/ D
2 Gang 1 Way Switch with LED indicator
10AX 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16A/ NS
Single 2-Pin Socket without Shutter
16A 250V
174×80×50mm; 24Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16A/ 2/ NS
Twin 2-Pin Socket without Shutter
16A 250V
174×80×50mm; 14Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16A/ 3/ NS
Triple 2-Pin Socket without Shutter
16A 250V
174×80×50mm; 12Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16A/ 4/ NS
Quadruple 2-Pin Socket without Shutter
16A 250V
174×80×50mm; 8Pcs/ Box
480×335×363mm; 108cs/ Ctn

SOK | Beyond Safety. Series M20

M20/ 16U/ NS
Single Schuko Socket without Shutter
16A 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16U/ S
Single Schuko Socket with Shutter
16A 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16U/ 2/ NS
Twin Schuko Socket without Shutter
16A 250V
174×80×50mm; 10Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16U/ 2/ S
Twin Schuko Socket with Shutter
16A 250V
174×80×50mm; 10Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16U/ 3/ NS
Triple Schuko Socket without Shutter
16A 250V
174×80×50mm; 8Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16U/ 3/ S
Triple Schuko Socket with Shutter
16A 250V
174×80×50mm; 8Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ 16U/ 4/ S
Quadruple Schuko Socket with Shutter
16A 250V
174×80×50mm; 6Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ TV
1 Gang TV Socket
16A 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ TEL/ 1
1 Gang TEL Socket
16A 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

M20/ LAN/ 1
1 Gang LAN Socket
16A 250V
174×80×50mm; 18Pcs/ Box
480×335×363mm; 108cs/ Ctn

Series M44

M44/ L1/ 1/ 16U/ NS

√ UV Resistant √ Water Proof: IP44

SOK | Beyond Safety.

Strictly follow IP44 certificate requirements.

Cable installation is tooling-free for the requirement of water-proof.



Outer thickness is increased to 2mm for hard-duty environment outdoors.

More space inside the wiring box for more complex wiring.

Earthing terminal is provided inside the box for complete protection outdoors.

Fire-resisted (850 degrees, equal to Class V0) back-housing material for living parts.

Sockets with Temper-Resistant system can be chosen to protect children from electric shock.

All switches can be equipped with LED locator as an option.

SOK | Beyond Safety. Series M44

M44/ L1/ 1
1 Gang 1 Way Switch
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 2
1 Gang 2 Way Switch
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 1/ D
1 Gang 1 Way Switch with LED indicator
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L4
1 Gang Intermediate Switch
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L2/ 1
2 Gang 1 Way Switch
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L2/ 1/ D
2 Gang 1 Way Switch with LED indicator
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

Beyond Safety.

M44/ L1/ 1/ L1/ 1
Block 10SW switch +10SW switch
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 1/ L2/ 1
Block 10SW switch +20SW switch
10AX 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

SOK | Beyond Safety. Series M44



M44/ 16U/ NS
Single Schuko Socket without Shutter
16A 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ 16U/ S
Single Schuko Socket with Shutter
16A 250V
188×150×48mm; 18Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ 16U/ 2/ NS
Twin Schuko Socket without Shutter
16A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ 16U/ 2/ S
Twin Schuko Socket with Shutter
16A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ 16U/ 3/ NS
Triple Schuko Socket without Shutter
16A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ 16U/ 3/ S
Triple Schuko Socket with Shutter
16A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn



M44/ L1/ 1/ 16U/ NS
Block single socket +10SW switch
16×10A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 1/ 16U/ /1 /S
Block single socket +10SW switch with shutter
16×10A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 2/ 16U/ NS
Block single socket +10SW switch
16×10A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

SOK | Beyond Safety. Series M44

M44/ L1/ 2/ 16U/ 1/ S
Block single socket +10SW switch with shutter
16×10A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 1/ 16U/ 2/ NS
Block twin socket +10SW switch
16×10A 250V
188×150×48mm; 6Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 1/ 16U/ 2/ S
Block twin socket +10SW switch with shutter
16×10A 250V
188×150×48mm; 6Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 2/ 16U/ 2/ NS
Block twin socket +10SW switch
16×10A 250V
188×150×48mm; 6Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L1/ 2/ 16U/ 2/ S
Block twin socket +10SW switch with shutter
16×10A 250V
188×150×48mm; 6Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L2/ 1/ 16U/ NS
Block single socket +20W switch
16×10A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L2/ 1/ 16U/ 1/ S
Block single socket +20W switch
16×10A 250V
188×150×48mm; 8Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L2/ 2/ 16U/ 2/ NS
Block twin socket +10ZW switch
16×10A 250V
188×150×48mm; 6Pcs/ Box
474×315×319mm; 128cs/ Ctn

M44/ L2/ 1/ 16U/ 2/ S
Block twin socket +20W switch with shutter
16×10A 250V
188×150×48mm; 6Pcs/ Box
474×315×319mm; 128cs/ Ctn

SOK | Beyond Safety.

INTRODUCE

Guangdong Jinli Electrical Appliance Was established in 1985. As one of the biggest manufacturer for electrical products in China, we mainly produce wall switches & sockets, exhaust fans and distribution boxes.

Our company covers 300,000 square meters, with over 1500 employee. The enterprise has got the certification of ISO9001, ISO14000 and International safety approval CE, CB, SASO & ROHS. Our company specialized in OEM & ODM.

We have OEM for the famous brands in the world. All of these brands are the top 5 in their markets. The experience ensures us to offer you the best service.

ISO9001 ISO14000 CE CB RoHS

GUANGDONG JINLI ELECTRICAL APPLIANCE CO., LTD.